



Specifications

| Model | GS-3384 RT | |
|--|----------------|---------|
| Measurements | US | Metric |
| Working height maximum* | 39 ft | 12.06 m |
| A Platform height maximum | 33 ft | 10.06 m |
| B Platform height - stowed** | 5 ft 1 in | 1.55 m |
| C Platform length: | | |
| outside, extended - single deck | 13 ft .5 in | 3.98 m |
| outside, extended - dual deck | 17 ft 6.25 in | 5.34 m |
| D Slide-out platform extension deck - front | 5 ft | 1.52 m |
| E Slide-out platform extension deck - rear | 4 ft | 1.22 m |
| F Platform width - outside | 6 ft | 1.83 m |
| G Height - stowed:folding guardrails | 8 ft 9.5 in | 2.68 m |
| rails lowered | 6 ft 6.75 in | 2.0 m |
| H Length - stowed: single deck | 12 ft 11.25 in | 3.94 m |
| dual deck | 13 ft 5 in | 3.98 m |
| with outriggers | 16 ft | 4.88 m |
| I Width: standard tires | 7 ft | 2.13 m |
| high flotation tires | 7 ft 11 in | 2.41 m |
| A Wheelbase | 9 ft 4 in | 2.84 m |
| k Ground clearance - center | 13 in | .33 m |

Productivity

| | | |
|---|--------------|------------|
| Maximum platform occupancy | 7 | 7 |
| Lift capacity | 2,500 lbs | 1,134 kg |
| Lift capacity - extension deck | 500 lbs | 227 kg |
| Drive speed - stowed | 4.0 mph | 6.4 km/h |
| Drive speed - raised | 0.7 mph | 1.1 km/h |
| Gradeability - stowed*** | 50% | |
| Maximum outrigger leveling: front to back | 7° | |
| side to side | 12° | |
| Turning radius - inside | 10 ft 1.5 in | 3.09 m |
| Turning radius - outside | 19 ft 6 in | 5.94 m |
| Raise/lower speed | 45/29 sec | |
| Controls | proportional | |
| Drive | four wheel | |
| Tires - foam-filled rough terrain | 10 x 31 in | 25 x 79 cm |

Power

| | |
|---------------------------|---|
| Power source | Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW) |
| | Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW) air cooled |
| Auxiliary Power unit | 12 V DC |
| Fuel tank capacity | 30 gal 113.6 L |
| Hydraulic system capacity | 30 gal 113.6 L |

Weight****

| | | |
|-----------------|------------|----------|
| | 12,005 lbs | 5,445 kg |
| with outriggers | 13,680 lbs | 6,205 kg |

Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking.

*** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

**** Weight will vary depending on options and/or country standards.

Features

Standard Features

Measurements

- 39 ft (12.06 m) working height
- Up to 2,500 lbs (1,134 kg) lift capacity

Productivity

- 156.5 x 72 in (3.98 x 1.83 m) steel frame platform
- 60 in (1.52 m) extension deck
- Replaceable aluminum deck
- Folding guardrails
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Full height swing gate
- Two self-closing gates
- 4WD
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires (eco fill)
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

Power

- Deutz diesel 49 hp (36kW)

Options & Accessories

Productivity Options

- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Automatic leveling hydraulic outriggers
- Air line to platform
- Foam filled non-marking rough terrain tires 10 x 31 in (25 x 79 cm)
- High flotation air-filled tires 17 x 33 in (43 x 84 cm)
- High flotation foam-filled tires 16 x 33 in (41 x 84 cm)
- Dual flashing beacons
- Motion alarm
- Biodegradable hydraulic oil

Power Options

- Ford gas/LPG 75 hp (56 kW)
- Deutz diesel 49 hp (36 kW)
- AC, 2000 Watt generator (120 V / 60 Hz)
- Cold weather package
- Hydraulic oil cooler
- Diesel catalytic scrubber muffler
- LPG steel tank only, 33.5 lb capacity
- Welder ArcPro 275 heavy duty (includes hydraulic oil cooler)
- Welder ready package (includes hydraulic oil cooler)



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Telephone +44 (0)1476 584333
Fax +44 (0)1476 584334
Email: AWP-InfoEurope@terex.com

Distributed By: